



POCKET PROREADER RF VISUAL READING DEVICE



The Pocket ProReader RF is available in two versions — one to read ProRead™ (ARB® VI); the other capable of reading ProRead (ARB VI), Sensus ECR® II and III* encoder registers.



The Pocket ProReader RF is a compact visual reading device designed for reading remote receptacle pads. With the Pocket ProReader RF, meter readers can test new installations, obtain readings and meter identification numbers in a faster, more efficient manner and readings can be transmitted directly to a CE5320 handheld with a radio frequency receiver. Reading remote pads is as simple as touching the pad and reading the information on the screen.

The Pocket ProReader RF can be conveniently carried in a pocket or clipped to a belt.

- KEY FEATURES**
- Meter readings may be reviewed and re-transmitted
 - Audible and displayed error messages
 - Displays meter reading and the programmed meter identification number
 - Serves as an excellent meter reading tool for wall mount receptacles
 - Can be used as an installation testing tool
 - Compatible with Neptune's ARB® N_SIGHT™ Mobile meter reading software
 - Readings are transmitted via 914 MHz to CE5320 handheld computers with HR2650i RF receivers

STANDARD FEATURES

- Single device designed for reading ProRead(ARB VI), ECR II and III* encoder registers
- Transmits meter readings directly to the CE5320 handheld unit by unlicensed radio frequency
- Capable of storing up to five meter readings in memory
- Acknowledges completed reads with a short tone and erroneous reads are signaled with a longer tone
- Unit displays the meter reading and the register identification number
- Powerful rechargeable battery capable of a full day of reading
- Transmits data over an unlicensed frequency at 914 MHz

WARRANTY

Neptune provides a limited warranty with respect to its Pocket ProReader RF for performance, materials and workmanship. Hardware maintenance agreements are also available.

* The ECR® III register is supported when programmed with the same format used in the "6 wheel ECR II register."

HARDWARE

- Power Supply
 - Uses 3 Ni-Cad AA rechargeable battery pack
 - Fully charged battery sufficient for 800-900 meter readings
 - Battery is rechargeable with a simple 120V wall charger rated for 4.5V@85mA / 4.35@200mA
 - Battery can be recharged without taking it out of the unit
 - Equipped with an on/off switch
- Memory
 - OTP: 32K ROM
 - RAM: 256 x 8 Bytes
- Display
 - 16 column x 2 lines LCD
 - Auto Temperature Compensation
- Keypad
 - 2 large keys, pillow embossed and waterproof
 - Function keys clearly marked
- Reader Head
 - Inductive probe reads ProRead (ARB VI), Sensus ECR II and III*
- RF Transmitter
 - Built-in unlicensed 914 MHz RF transmitter
 - Minimum 6 ft. transmission range
 - Meets FCC Part 15 and Industry Canada requirements
- Dimensions
 - Length, total: 6.25"
 - Width: 2.72"
 - Depth: 1.69"
 - Weight: 13 oz.

** The ECR® III register is supported when programmed with the same format used in the "6 wheel ECR II register."*

ENVIRONMENTAL

- Temperature
 - Operating: -20°C to +50°C
 - Storage: -40°C to +80°C
- Water Resistance
 - Withstands unlimited spray or splash such as rain
- Chemical Resistance
 - Acids, alcohols, glycols and oils
- Impact
 - Withstands repeated drops from a height of one metre on concrete
- Electrostatic Discharge
 - Withstands a 16 Kv discharge without loss of data
- Accessory Equipment
 - Wall charger

Neptune engages in ongoing research and development to improve and enhance its products. Therefore, Neptune reserves the right to change product or system specifications without notice.

Neptune Technology Group Inc.

1600 Alabama Highway 229
Tallahassee, AL 36078
USA
Tel: (800) 645-1892
Fax: (334) 283-7293

Neptune Technology Group (Canada) Ltd.

7275 West Credit Avenue
Mississauga, Ontario
L5N 5M9
Canada
Tel: (905) 858-4211
Fax: (905) 858-0428

Neptune Technology Group Inc.

Ejército Nacional No. 418
Piso 12, Desp. 1201-1202
Col. Chapultepec Morales
Delegación Miguel Hidalgo
11570 México, Distrito Federal
Tel: (525) 55203 5294 / (525) 55203 5708
Fax: (525) 55203 6503



NEPTUNE
TECHNOLOGY GROUP

neptunetg.com